

LDI-1310-DFB-25G-15

Preliminary

OVERVIEW

LDI-1310-DFB-25G-15 is the high-speed MQW DFB laser diode coupled to an optical fiber and packaged into a hermetic case.

MAIN FEATURES

- Wavelength: 1310 nm
- Cavity type: DFB
- Data rate up to 25 Gbps
- Optical power: 15 mW in CW mode in SM fiber G.657.A1
- Package types: coaxial, coaxial with bracket
- Built-in monitor photodiode

APPLICATIONS

- Optical fiber communication systems with data rate up to 25 Gbps
- Laser systems

ORDERING INFORMATION

LDI-1310-DFB-25G-15-X-12-X-X-X-X

Case type

U: compact coaxial (pulse mode only)
B: compact coaxial with double-sided bracket
 Other type on request

Fiber type

SM1: SM, G.657.A1, [Corning SMF-28 Ultra](#), furcation tubing \varnothing 0.9 mm or **BSM1** \varnothing 0.25mm
SM3: SM, G.657.B3, [Corning ClearCurve ZBL](#), furcation tubing \varnothing 0.9 mm or **BSM3** \varnothing 0.25mm
SMP13: PM, [Fujikura SM13](#), PANDA type, furcation tubing \varnothing 0.9 mm
 Other type on request

Connector type

FA: FC/APC (SM1, SM3, SMP13)
SA: SC/APC (SM1)
N: no connector
 Other type: on request

Test measurements

CW: CW mode (electro-optical parameters at $T=25\pm 5$ C and spectrum)
P: pulse mode (10 μ s; duty cycle = 1%)
CWP: both CW and pulse modes

Fiber length

0.5: 500 \pm 50 mm
1.0: 1000 \pm 100 mm
 Other length on request

LDI-1310-DFB-25G-15

ABSOLUTE MAXIMUM RATINGS






Parameter		Value	Unit	Conditions
Laser diode forward current	I_{FL}	105	mA	CW
Laser diode reverse voltage	V_{RL}	2	V	
Photodiode reverse voltage	V_{RP}	20	V	
Photodiode forward current	I_{FP}	2	mA	
Operating temperature	T_{OP}	-40 - +85	°C	Package U, B
Storage temperature	T_{stg}	-40 - +85	°C	
Soldering temperature	T_{sold}	260	°C	max. 5 seconds

ELECTRICAL-OPTICAL CHARACTERISTICS (T = 25 °C)

Parameter		MIN	TYP	MAX	Unit	Conditions
Wavelength	λ	1295	1310	1325	nm	CW, I _{op} = 100 mA
Spectral width	$\Delta\lambda$		0.12		nm	CW, I _{op} = 100 mA, -20 dB, OSA
Spectral width	$\Delta\lambda$		1		MHz	CW, I _{op} = 100 mA, delayed self-heterodyne method
Wavelength-temperature coeff.	$d\lambda/dT$		0.12		nm/°C	
Side-mode suppression ratio	SMSR	40	50		dB	CW, I _{op} = 100 mA
Threshold current	I_{th}		6	10	mA	CW
Optical power (CW)	P _{cw}	15			mW	CW, I _{op} = 100 mA, SM
Slope efficiency	S_e	0.10	0.13		W/A	CW, SM
Operating voltage	V_{op}		1.6	2.0	V	CW, I _{op} = 100 mA
Tracking error	E_r		0.5	1.0	dB	CW, P = 3 mW; T = -40 ÷ +85 °C
Rise and fall times	t_r, t_f			25	ps	20%-80%, P _{av} = 4 mW
Monitoring output current (PD)	I_m	0.1	1.0	5.0	mA	CW, I _{op} = 100 mA, V _{rd} = 5V
Capacitance (PD)	C_t		10		pF	V _{rd} = 1 V, f = 1 MHz
Dark current (PD)	I_d			100	nA	V _{rd} = 1 V

Tracking error $E_r = \max [10 \lg [P(T)/P(25^\circ\text{C})]]$, $I_m = \text{const}$, $T = T_{\min} \div T_{\max}$

LDI-1310-DFB-25G-15




LDI-1310-DFB-25G-15




PACKAGE U

BACK VIEW



PINOUT
#12




Download more information

Drawing


3D model

Application Notes




PACKAGE B

BACK VIEW



PINOUT
#12



Download more information

Drawing

3D model

Application Notes

LDI-1310-DFB-25G-15

Characteristics, data, materials and structures specified in this datasheet are subject to change without notice. Please refer to the latest specification before use of the products.

Safety and handling cautions

1. Avoid smashing and burning of the module. Avoid storing and using the module in conditions where water, organic solvents or aggressive acids or bases may contact the module or where there is a possibility of exposure to corrosive gases, explosive gases, dust, salinity or other harsh conditions. The module should be disposed as special industrial waste.
2. Exceeding absolute maximum ratings even for a short time can cause permanent damage of the module.
3. The module is sensitive to and can be broken by ESD (static electricity).

Conflict Minerals Policy Statement

LasersCom LLC achieves business objectives and customer needs with social responsibility. We do not support or contribute to the violence and human rights violations associated with the mining of conflict minerals coming from Conflict Regions according to US "Dodd-Frank Act". When possible, our suppliers' conflict mineral statements are reviewed. We do not directly purchase Conflict Minerals from any source and do not knowingly procure any parts and products containing Conflict Minerals from Conflict Regions.

RoHS Compliance Statement

Restriction of Hazardous Substances (RoHS) directive (Directive 2011/65/EC amended with Directive (EU) 2015/863) is the directive aimed at reducing the harmful environmental impact of waste electrical equipment by restricting the use of known dangerous substances. Based on information received from our supply sources, LasersCom LLC hereby states that the banned substances listed in the RoHS directive are not found in the parts and materials used above the threshold level listed other than exceptions approved by the European Commission.

REACH Compliance Statement

Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) is a European Union regulation 1907/2006/EC that addresses the production and use of chemical substances, and their potential impacts on human health and the environment. Based on information received from our supply sources, LasersCom LLC hereby states compliance of the parts and materials used in manufacturing to REACH regulation. LasersCom LLC does not manufacture or import any substances or preparations as defined under REACH.