

PDI-250-P5-LC

OVERVIEW

PDI-250-P5-LC is the InGaAs PIN photodiode with the extended spectral range coupled to an optical fiber and packaged into a hermetic case

MAIN FEATURES

- Maximum optical input power: 5 mW
- Cut-off wavelength: >2150 nm
- Typical peak responsivity: 1.3 A/W
- Package types: coaxial with or without bracket
- Low back reflection, return loss RL > 50 dB

APPLICATIONS

- Optical fiber communication systems
- Spectroscopy

ORDERING INFORMATION

PDI-250-P5-LC - X-X-7-X-X-X

Optical matching

R50: back reflection -50 dB (SM06, SM1 or SM3 fiber, FA, SA or N connector)

R30: back reflection -30 dB (MM5 and MM6 fiber)

Case type

U: compact coaxial

B: compact coaxial with double-sided bracket

Fiber type

SM06: SM, [Corning Hi-1060](#), furcation tubing Ø0.9 mm

SM1: SM, G.657.A1, [Corning SMF-28 Ultra](#), furcation tubing Ø0.9 mm or **BSM1** Ø0.25mm

SM3: SM, G.657.B3, [Corning ClearCurve ZBL](#), furcation tubing Ø0.9 mm or **BSM3** Ø0.25mm

SMT: SM, [Corning Titania-Clad](#), furcation tubing Ø0.9 mm, ultrasmall bending radius 2.5 mm

MM5: MM, [50/125. OM2](#), furcation tubing Ø0.9 mm

MM6: MM, [62.5/125. OM1](#), furcation tubing Ø0.9 mm

MM105: MM, 105/125, NA=0.22, [Coherent S105/125-22A](#), furcation tubing Ø0.9 mm

MM200: MM, 200/220, NA=0.22, [YOFC SI 200/220-22/500](#), furcation tubing Ø0.9 mm

Other type: on request

Connector type

FA: FC/APC (SM06, SM1, SM3, SMT)

SA: SC/APC (SM1)

N: no connector

Other type: on request

FU: FC/UPC (SM06, SM1, SM3, SMT, MM5, MM6)

SU: SC/UPC (SM1)

Fiber length

0.5: 500+/-50 mm

1.0: 1000+/-100 mm

Other length: on request

PDI-250-P5-LC

ABSOLUTE MAXIMUM RATINGS






Parameter		Value	Unit	Conditions
Maximum optical input power	P_{\max}	5	mW	
Reverse voltage	V_R	1	V	
Forward current	I_F	1	mA	
Operating temperature	T_{op}	$-40 \div +85$	$^{\circ}\text{C}$	
Storage temperature	T_{stg}	$-40 \div +85$	$^{\circ}\text{C}$	
Soldering temperature	T_{sold}	260	$^{\circ}\text{C}$	Max. 5 seconds

ELECTRICAL-OPTICAL CHARACTERISTICS (T = 25 $^{\circ}\text{C}$)


Parameter		Min	Typ	Max	Unit	Conditions
Responsivity	R	0.33	0.41		A/W	$\lambda = 900 \text{ nm}, V_R = 0 \text{ V}$
		0.74	0.92			$\lambda = 1300 \text{ nm}, V_R = 0 \text{ V}$
		0.87	1.05			$\lambda = 1550 \text{ nm}, V_R = 0 \text{ V}$
			1.20			$\lambda = 1900 \text{ nm}, V_R = 0 \text{ V}$
Wavelength of peak responsivity	λ	1850	1950	2050	nm	
Wavelength cut-off	λ_c	2150			nm	-3 dB
Return loss	R50	45	50		dB	SM1, SM3
	R30	25	30			MM5, MM6
Operating voltage	V_{op}		0.25			
Dark current	I_d		0.2	1	μA	$V_R = 0.25 \text{ V}$
Shunt impedance		400	800		kOhm	$V_R = 10 \text{ mV}$
Capacitance	C		40		pF	$V_R = 0 \text{ V}$
Peak specific detectivity	D^*		2.9×10^{11}		$\text{cm} \sqrt{\text{Hz}} / \text{W}$	
Peak NEP	NEP		7.8×10^{-14}		$\text{W} / \sqrt{\text{Hz}}$	

PDI-250-P5-LC

CHARACTERISTICS (T = 25 °C)





PDI-250-P5-LC



PACKAGE U


BACK VIEW

PINOUT
#7Download more
information

Drawing



3D model

Application Notes



PACKAGE B

BACK VIEW

PINOUT
#7Download more
information

Drawing

3D model

Application Notes

PDI-250-P5-LC

Characteristics, data, materials and structures specified in this datasheet are subject to change without notice. Please refer to the latest specification before use of the products.

Safety and handling cautions

1. Avoid smashing and burning of the module. Avoid storing and using the module in conditions where water, organic solvents or aggressive acids or bases may contact the module or where there is a possibility of exposure to corrosive gases, explosive gases, dust, salinity or other harsh conditions. The module should be disposed as special industrial waste.
2. Exceeding absolute maximal ratings even for a short time can cause permanent damage of the module.
3. The module is sensitive to and can be broken by ESD (static electricity).

Conflict Minerals Policy Statement

LasersCom LLC achieves business objectives and customer needs with social responsibility. We do not support or contribute to the violence and human rights violations associated with the mining of conflict minerals coming from Conflict Regions according to US "Dodd-Frank Act". When possible, our suppliers' conflict mineral statements are reviewed. We do not directly purchase Conflict Minerals from any source and do not knowingly procure any parts and products containing Conflict Minerals from Conflict Regions.

RoHS Compliance Statement

Restriction of Hazardous Substances (RoHS) directive (Directive 2011/65/EC amended with Directive (EU) 2015/863) is the directive aimed at reducing the harmful environmental impact of waste electrical equipment by restricting the use of known dangerous substances. Based on information received from our supply sources, LasersCom LLC hereby states that the banned substances listed in the RoHS directive are not found in the parts and materials used above the threshold level listed other than exceptions approved by the European Commission.

REACH Compliance Statement

Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) is a European Union regulation 1907/2006/EC that addresses the production and use of chemical substances, and their potential impacts on human health and the environment. Based on information received from our supply sources, LasersCom LLC hereby states compliance of the parts and materials used in manufacturing to REACH regulation. LasersCom LLC does not manufacture or import any substances or preparations as defined under REACH.